



CONFIGURATION

X	Control	Not Adjustable
A	Cracking Pressure	4 psi (0,3 bar)
N	Seal Material	Buna-N
	Material/Coating	

Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

TECHNICAL DATA

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

CONFIGURATION OPTIONS

Model Code Example: CXHAXAN

CONTROL	(X)	CRACKING PRESSURE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
X	Not Adjustable	A	4 psi (0,3 bar)	N	Buna-N	/LH	Mild Steel, Zinc-Nickel
		B	15 psi (1 bar)	E	EPDM	JAP	Stainless Steel, Passivated
		C	30 psi (2 bar)	V	Viton		Standard Material/Coating
		D	50 psi (3,5 bar)				
		F	100 psi (7 bar)				
		G	150 psi (10,5 bar)				
		Z	1 psi (0,07 bar)				