



### CONFIGURATION

X	Control	Not Adjustable
A	Cracking Pressure	4 psi (0,3 bar)
N	Seal Material	Buna-N
	Material/Coating	

### TECHNICAL DATA

NOTE:

cavidad	T-16A	DATA
Series	3	MAY
Capacity	320 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.	
Valve Hex Size	31,8 mm	
Valve Installation Torque	203 - 217 Nm	
Model Weight	0.42 kg.	
Seal kit - Cartridge	Buna: 990-016-007	
Seal kit - Cartridge	EPDM: 990-016-014	
Seal kit - Cartridge	Polyurethane: 990-016-002	
Seal kit - Cartridge	Viton: 990-016-006	
Seal kit - Cartridge	Buna: 990-016-007	
Seal kit - Cartridge	EPDM: 990-016-014	
Seal kit - Cartridge	Polyurethane: 990-016-002	
Seal kit - Cartridge	Viton: 990-016-006	

CONFIGURATION. SEE  
CONFIGURATION SECTION.

## OPTION SELECTION EXAMPLE: CXHAXAN

CONTROL	(X) CRACKING PRESSURE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>A</b> 4 psi (0,3 bar)	<b>N</b> Buna-N	<b>/LH</b> Mild Steel, Zinc-Nickel
L activador manual	F 100 psi (7 bar)	E EPDM	<b>/AP</b> Stainless Steel, Passivated
	G 150 psi (10,5 bar)	V Viton	Standard Material/Coating
	Z 1 psi (0,07 bar)		

### PERFORMANCE CURVES

