



CONFIGURATION

X	
C	30 psi (2 bar)
N	
Material/Coating	

/ 1 2

NOTE: DATA MAY VARY FROM TECHNICAL DATA SEE CONFIGURATION SECTION.

	T-16A
	3
	320 L/min.
	350 bar
110 SUS (24 cSt)	0,07 cc/min.
	31,8 mm
	203 - 217 Nm
	0.43 kg.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

OPTION SELECTION EXAMPLE: CXHAXCN

	(X)	(C)	(N)	MATERIAL/COATING	(/LH)
X	C 30 psi (2 bar)	N	/LH	-	
L	A 4 psi (0,3 bar)	E EPDM	/AP		
	B 15 psi (1 bar)	V		Standard Material/Coating	
	D 50 psi (3,5 bar)				
	E 75 psi (5 bar)				
	F 100 psi (7 bar)				
	G 150 psi (10,5 bar)				
	Z 1 psi (0,07 bar)				

TECHNICAL FEATURES

-
-
- 1 2 5000psi 350bar
- EPDM
- "AP"
- Sun

PERFORMANCE CURVES

