



Free-flow, side-to-nose cheater check valves function as a standard 2-port check valve in a 3-port cavity with port 3 of the cartridge blocked off. These valves are useful in circuits where a check valve is required in an existing three port cavity.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

CONFIGURATION OPTIONS

Model Code Example: CXIEXCN

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		C 30 psi (2 bar)		N Buna-N		Standard Material/Coating
		A 4 psi (0,3 bar)		V Viton		/AP Stainless Steel, Passivated
		B 15 psi (1 bar)				/LH Mild Steel, Zinc-Nickel
		D 50 psi (3,5 bar)				
		F 100 psi (7 bar)				
		Z 1 psi (0,07 bar)				