



Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

CONFIGURATION OPTIONS

Model Code Example: CXJALXCN

CONTROL	(L)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		C 30 psi (2 bar)		N Buna-N		Standard Material/Coating
X Not Adjustable		A 4 psi (0,3 bar)		E EPDM		JAP Stainless Steel, Passivated
		B 15 psi (1 bar)		V Viton		LH Mild Steel, Zinc-Nickel
		D 50 psi (3,5 bar)				
		F 100 psi (7 bar)				
		G 150 psi (10,5 bar)				
		Z 1 psi (0,07 bar)				