



CONFIGURATION

X	Control	Not Adjustable
A	Cracking Pressure	4 psi (0,3 bar)
N	Seal Material	Buna-N
	Material/Coating	

NOTE: DATA MAY VARY FROM TECHNICAL DATA. SEE CONFIGURATION SECTION.

cavidad	T-18A
Series	4
Capacity	610 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Model Weight	0.93 kg.
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

OPTION SELECTION EXAMPLE: CXJAXAN

CONTROL	(X) CRACKING PRESSURE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	A 4 psi (0,3 bar)	N Buna-N	/LH Mild Steel, Zinc-Nickel
L Standard Screw Adjustment	F 100 psi (7 bar)	E EPDM	/AP Stainless Steel, Passivated
	G 150 psi (10,5 bar)	V Viton	Standard Material/Coating
	Z 1 psi (0,07 bar)		

PERFORMANCE CURVES

