



**CONFIGURATION**

X	
A	4 psi (0,3 bar)
N	
Material/Coating	

PORT2  
OUTLET

PORT1  
INLET

/ 1 2

NOTE: DATA MAY VARY FROM TECHNICAL DATA. SEE CONFIGURATION SECTION.

	T-18A
	4
	610 L/min.
	350 bar
110 SUS (24 cSt)	0,07 cc/min.
	41,3 mm
	474 - 508 Nm
	0.93 kg.
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

## OPTION SELECTION EXAMPLE: CXJAXAN

	(X)	(A)	(N)	MATERIAL/COATING	(/LH)
<b>X</b>	<b>A</b> 4 psi (0,3 bar)	<b>N</b>	<b>/LH</b>	-	
<b>L</b>	<b>B</b> 15 psi (1 bar)	<b>E</b> EPDM	<b>/AP</b>		
	<b>C</b> 30 psi (2 bar)	<b>V</b>		Standard Material/Coating	
	<b>D</b> 50 psi (3,5 bar)				
	<b>E</b> 75 psi (5 bar)				
	<b>F</b> 100 psi (7 bar)				
	<b>G</b> 150 psi (10,5 bar)				

### TECHNICAL FEATURES

- 
- 
- 1 2 5000psi 350bar
- EPDM
- "AP"
- Sun

### PERFORMANCE CURVES

