



### CONFIGURATION

X	Control	Not Adjustable
C	Cracking Pressure	30 psi (2 bar)
N	Seal Material	Buna-N
	Material/Coating	

NOTE: DATA MAY VARY FROM TECHNICAL DATA. SEE CONFIGURATION SECTION.

cavidad	T-18A
Series	4
Capacity	610 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Model Weight	0.95 kg.
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

## OPTION SELECTION EXAMPLE: CXJAXCN

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
<b>X</b> Not Adjustable		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N		<b>/LH</b> Mild Steel, Zinc-Nickel	
<b>L</b> Standard Screw Adjustment		<b>F</b> 100 psi (7 bar)		<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated	
		<b>G</b> 150 psi (10,5 bar)		<b>V</b> Viton		Standard Material/Coating	
		<b>Z</b> 1 psi (0,07 bar)					

### PERFORMANCE CURVES

