



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-18AU
Series	4
Capacity	900 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Model Weight	0,95 kg
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Viton: 990-018-006
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Viton: 990-018-006

## OPTION SELECTION EXAMPLE: CXKAXCFGN

CONTROL	(X) CRACKING PRESSURE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>C</b> 30 psi (2 bar)	<b>N</b> Buna-N	Standard Material/Coating
	<b>F</b> 100 psi (7 bar)	<b>E</b> EPDM	<b>/AP</b> Stainless Steel, Passivated
	<b>G</b> 150 psi (10,5 bar)	<b>V</b> Viton	<b>/LH</b> Mild Steel, Zinc-Nickel
	<b>Z</b> 1 psi (0,07 bar)		

### PERFORMANCE CURVES

