



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-18AU
	4
	900 L/min.
	350 bar
110 SUS (24 cSt)	0,07 cc/min.
	41,3 mm
	474 - 508 Nm
	0.92 kg.
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Viton: 990-018-006
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Viton: 990-018-006

## OPTION SELECTION EXAMPLE: CXKAXCN

	(X)	(C)	(N)	MATERIAL/COATING
<b>X</b>	<b>C</b> 30 psi (2 bar)	<b>N</b>	Standard Material/Coating	
	A 4 psi (0,3 bar)	E EPDM	/AP	
	B 15 psi (1 bar)	V	/LH -	
	D 50 psi (3,5 bar)			
	E 75 psi (5 bar)			
	F 100 psi (7 bar)			
	G 150 psi (10,5 bar)			

### TECHNICAL FEATURES

- T-18A T-18AU
- EPDM
- 1 0.07cc/min
- 1 2 5000psi 350bar
- "/AP"
- Sun

### PERFORMANCE CURVES

