



Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|--------------------|
| Maximum Operating Pressure | 5000 psi |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 1 drops/min. |
| Valve Internal Hex Size | 3/16 in. |
| Seal kit - Cartridge | Buna: 990-382-007 |
| Seal kit - Cartridge | EPDM: 990-382-014 |
| Seal kit - Cartridge | Viton: 990-382-006 |

CONFIGURATION OPTIONS

Model Code Example: **CXZAXCN**

| CONTROL | (X) | CRACKING PRESSURE | (C) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|------------------|-----|-------------------|-----|---------------|-----|---------------------------------|
| X Not Adjustable | | C 30 psi (2 bar) | | N Buna-N | | Standard Material/Coating |
| | | | | E EPDM | | /AP Stainless Steel, Passivated |
| | | | | V Viton | | /LH Mild Steel, Zinc-Nickel |