



**CONFIGURATION**

<b>B</b>	Control	External 4-SAE Port
<b>C</b>	Spool Configuration	Normally Closed
<b>N</b>	Seal Material	Buna-N
	Material/Coating	

These pilot-stage, directional, 2-position, 2-way valves are hydraulically operated, spring-return cartridges and are available in either a normally open or normally closed configuration. These cartridges are designed for pilot flow

applications and utilize Sun's T-8A cavity so they can be used in conjunction with Sun's pilot-operated, main-stage valves.

**TECHNICAL DATA**

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	5 drops/min.
Minimum Pilot Pressure to Operate	See Technical Features
Pilot Control Port	See Control Options
Seal kit - Cartridge	Buna: 990-508-007
Seal kit - Cartridge	Viton: 990-508-006

**CONFIGURATION OPTIONS**

**Model Code Example: DAAHBCN**

CONTROL	(B) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
<b>B</b> External 4-SAE Port	<b>C</b> Normally Closed	<b>N</b> Buna-N	Standard Material/Coating
<b>A</b> External 1/8 NPTF Port	<b>H</b> Normally Open	<b>V</b> Viton	<b>/AP</b> Stainless Steel, Passivated
<b>D</b> External 1/8 BSPP Port			