



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-8A
Series	P
Capacity	1 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Minimum Pilot Pressure to Operate	See Technical Features
Pilot Control Port	See Control Options
Valve Hex Size	22,2 mm
Valve Installation Torque	27 - 33 Nm
Seal kit - Cartridge	Buna: 990-508-007
Seal kit - Cartridge	Viton: 990-508-006
Seal kit - Cartridge	Buna: 990-508-007
Seal kit - Cartridge	Viton: 990-508-006

# OPTION SELECTION EXAMPLE: DAAHBCN

CONTROL	(B) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
<b>B</b> External 4-SAE Port	<b>C</b> normalmente cerrado	<b>N</b> Buna-N	Standard Material/Coating
A External 1/8 NPTF Port	H normalmente abierto	V Viton	/AP Stainless Steel, Passivated
D External 1/8 BSPP Port			

## PERFORMANCE CURVES

