



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Minimum Pilot Pressure to Operate	See Technical Features
Pilot Control Port	See Control Options
Seal kit - Cartridge	Buna: 990-509-007
Seal kit - Cartridge	Viton: 990-509-006
Seal kit - Cartridge	Buna: 990-509-007
Seal kit - Cartridge	Viton: 990-509-006

**CONFIGURATION OPTIONS**

**Model Code Example: DBAHBCN**

CONTROL	(B) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
<b>B</b> External 4-SAE Port	<b>C</b> Normally Open 1 to 3, Closed 1 to 2	<b>N</b> Buna-N	Standard Material/Coating
<b>A</b> External 1/8 NPTF Port	<b>H</b> Normally Open 1 to 2, Closed 1 to 3	<b>V</b> Viton	<b>/AP</b> Stainless Steel, Passivated
<b>D</b> External 1/8 BSPP Port			<b>/LH</b> Mild Steel, Zinc-Nickel