



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-9A
Series	P
Capacity	1 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Valve Hex Size	22,2 mm
Valve Installation Torque	27 - 33 Nm
Model Weight	0.27 kg.
Seal kit - Cartridge	Buna: 990-109-007
Seal kit - Cartridge	EPDM: 990-009-014
Seal kit - Cartridge	Viton: 990-109-006
Seal kit - Cartridge	Buna: 990-109-007
Seal kit - Cartridge	EPDM: 990-009-014
Seal kit - Cartridge	Viton: 990-109-006

OPTION SELECTION EXAMPLE: DBAMLCN

CONTROL

- L** Twist/Lock (Detent) Manual Override
- D** Twist/Lock (Dual) Manual Override
- T** Twist (Momentary) Manual Override

(L)

SPOOL CONFIGURATION

- C** Normally Open 1 to 3, Closed 1 to 2
- H** Normally Open 1 to 2, Closed 1 to 3

(C)

SEAL MATERIAL

- N** Buna-N
- E** EPDM
- V** Viton

(N)

PERFORMANCE CURVES

