



3 4 6 3 5000psi(350 bar)

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-61A
	1
	28 - 40 L/min.
	350 bar
	12 bar
	0,33 cc
110 SUS (24 cSt)	30 cc/min.@70 bar
	22,2 mm
	41 - 47 Nm
	0,20 kg
Seal kit - Cartridge	Buna: 990-061-007
Seal kit - Cartridge	Polyurethane: 990-061-002
Seal kit - Cartridge	Viton: 990-061-006
Seal kit - Cartridge	Buna: 990-061-007
Seal kit - Cartridge	Polyurethane: 990-061-002
Seal kit - Cartridge	Viton: 990-061-006

OPTION SELECTION EXAMPLE: DCCCXCYN

	(X)	(Y)	(N)	MATERIAL/COATING
X	Y	A-B-T	N	Standard Material/Coating
	A	A-T	V	/AP
	B	B-T		/LH -
	C			
	F	A-B-T		
	H			
	N			
	R	P-A-B		
	T	P-T		
	W	A B T		

TECHNICAL FEATURES

- 5000psi 350bar x y 5 6
-
-
- 5,6
-
- Sun

PERFORMANCE CURVES

