



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|  |                           |
|--|---------------------------|
| cavidad  | T-61A                     |
| Series   | 1                         |
| Capacity                                       | 28 - 40 L/min.            |
| Maximum Operating Pressure                     | 350 bar                   |
| Minimum Pilot Pressure Required to Shift Valve | 12 bar                    |
| Maximum Valve Leakage at 110 SUS (24 cSt)      | 30 cc/min.@70 bar         |
| Pilot Volume Displacement                      | 0,33 cc                   |
| Valve Hex Size                                 | 22,2 mm                   |
| Valve Installation Torque                      | 41 - 47 Nm                |
| Model Weight                                   | 0,20 kg                   |
| Seal kit - Cartridge                           | Buna: 990-061-007         |
| Seal kit - Cartridge                           | Polyurethane: 990-061-002 |
| Seal kit - Cartridge                           | Viton: 990-061-006        |

## OPTION SELECTION EXAMPLE: DCCCXN

CONTROL

(X)

SEAL MATERIAL

(N)

MATERIAL/COATING

X piloto estándar

N Buna-N

Standard Material/Coating

V Viton

/AP Stainless Steel, Passivated

/LH Mild Steel, Zinc-Nickel

### PERFORMANCE CURVES

