



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-61A
Series	1
Capacity	40 - 50 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	12 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,82 cc
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.21 kg.
Seal kit - Cartridge	Buna: 990-061-007
Seal kit - Cartridge	Polyurethane: 990-061-002
Seal kit - Cartridge	Viton: 990-061-006

OPTION SELECTION EXAMPLE: DCCDXCN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X piloto estándar	C Blocked Crossover	N Buna-N	Standard Material/Coating
	H Open Crossover	V Viton	/AP Stainless Steel, Passivated
	T Tandem Crossover		/LH Mild Steel, Zinc-Nickel
	X P to B and A to T Crossover		

PERFORMANCE CURVES

