



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-61A
Series	1
Capacity	28 - 40 L/min.
Minimum Pilot Pressure Required to Shift Valve	12 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,33 cc
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0,20 kg
Seal kit - Cartridge	Buna: 990-061-007
Seal kit - Cartridge	Polyurethane: 990-061-002
Seal kit - Cartridge	Viton: 990-061-006

OPTION SELECTION EXAMPLE: DCCFXCXN

CONTROL	(X)	SPOOL CONFIGURATION	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
X piloto estándar		C Blocked Center		N Buna-N		Standard Material/Coating
		A A to T Center		V Viton		/AP Stainless Steel, Passivated
		B B to T Center				/LH Mild Steel, Zinc-Nickel
		H Open Center				
		R Regen Center				
		T Tandem Center				
		W A and B Bleed to T Center				
		X P to A and B to T Center				
		Y A and B to T Center				

PERFORMANCE CURVES

