



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	10,5 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,98 cc
Seal kit - Cartridge	Buna: 990-062-007
Seal kit - Cartridge	Polyurethane: 990-062-002
Seal kit - Cartridge	Viton: 990-062-006
Seal kit - Cartridge	Buna: 990-062-007
Seal kit - Cartridge	Polyurethane: 990-062-002
Seal kit - Cartridge	Viton: 990-062-006

CONFIGURATION OPTIONS

Model Code Example: DCDCXCYN

CONTROL (X)	SPOOL CONFIGURATION (C)	SEAL MATERIAL (N)	MATERIAL/COATING
X piloto estándar	C Blocked Center	N Buna-N	Standard Material/Coating
	A A to T Center	E EPDM	/AP Stainless Steel, Passivated
	B B to T Center	V Viton	/LH Mild Steel, Zinc-Nickel
	H Open Center		
	N P to A and B to T Center		
	R Regen Center		
	T Tandem Center		
	W A and B Bleed to T Center		
	Y A and B to T Center		