



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-62A
Series	2
Capacity	38 - 120 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	10,5 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,98 cc
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Model Weight	0,35 kg
Seal kit - Cartridge	Buna: 990-062-007
Seal kit - Cartridge	Polyurethane: 990-062-002
Seal kit - Cartridge	Viton: 990-062-006
Seal kit - Cartridge	Buna: 990-062-007
Seal kit - Cartridge	Polyurethane: 990-062-002
Seal kit - Cartridge	Viton: 990-062-006

## OPTION SELECTION EXAMPLE: DCDCXCYN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X piloto estándar	C Blocked Center	N Buna-N	Standard Material/Coating
	A A to T Center	E EPDM	/AP Stainless Steel, Passivated
	B B to T Center	V Viton	/LH Mild Steel, Zinc-Nickel
	H Open Center		
	N P to A and B to T Center		
	R Regen Center		
	T Tandem Center		
	W A and B Bleed to T Center		
	Y A and B to T Center		

### PERFORMANCE CURVES

