



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|---------------------------|
| cavidad | T-62A |
| Series | 2 |
| Capacity | 38 - 120 L/min. |
| Minimum Pilot Pressure Required to Shift Valve | 10,5 bar |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 30 cc/min.@70 bar |
| Pilot Volume Displacement | 0,98 cc |
| Valve Hex Size | 28,6 mm |
| Valve Installation Torque | 61 - 68 Nm |
| Model Weight | 0,35 kg |
| Seal kit - Cartridge | Buna: 990-062-007 |
| Seal kit - Cartridge | Polyurethane: 990-062-002 |
| Seal kit - Cartridge | Viton: 990-062-006 |
| Seal kit - Cartridge | Buna: 990-062-007 |
| Seal kit - Cartridge | Polyurethane: 990-062-002 |
| Seal kit - Cartridge | Viton: 990-062-006 |

OPTION SELECTION EXAMPLE: DCDFXCXYN

| CONTROL | (X) | SPOOL CONFIGURATION | (C) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|-------------------------|-----|-----------------------------|-----|-----------------|-----|---------------------------------|
| X Not Adjustable | | C Blocked Crossover | | N Buna-N | | Standard Material/Coating |
| | | A A to T Center | | E EPDM | | /AP Stainless Steel, Passivated |
| | | B B to T Center | | V Viton | | /LH Mild Steel, Zinc-Nickel |
| | | H Open Crossover | | | | |
| | | R Regen Center | | | | |
| | | T Tandem Center | | | | |
| | | W A and B Bleed to T Center | | | | |
| | | X P to A and B to T Center | | | | |
| | | Y A and B to T Center | | | | |

PERFORMANCE CURVES

