



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-63A
Series	3
Capacity	95 - 380 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	9 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	2,8 cc
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Model Weight	0.85 kg.
Seal kit - Cartridge	Buna: 990-063-007
Seal kit - Cartridge	EPDM: 990-063-014
Seal kit - Cartridge	Polyurethane: 990-063-002
Seal kit - Cartridge	Viton: 990-063-006

## OPTION SELECTION EXAMPLE: DCEXCXN

CONTROL	(X)	SPOOL CONFIGURATION	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> piloto estándar		<b>C</b> Blocked Center		<b>N</b> Buna-N		Standard Material/Coating
		<b>A</b> A to T Center		<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated
		<b>B</b> B to T Center		<b>V</b> Viton		
		<b>H</b> Open Center				
		<b>N</b> P to A and B to T Center				
		<b>R</b> Regen Center				
		<b>T</b> Tandem Center				
		<b>W</b> A and B Bleed to T Center				
		<b>Y</b> A and B to T Center				

### PERFORMANCE CURVES

