



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	9 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	2,8 cc
Seal kit - Cartridge	Buna: 990-063-007
Seal kit - Cartridge	EPDM: 990-063-014
Seal kit - Cartridge	Polyurethane: 990-063-002
Seal kit - Cartridge	Viton: 990-063-006
Seal kit - Cartridge	Buna: 990-063-007
Seal kit - Cartridge	EPDM: 990-063-014
Seal kit - Cartridge	Polyurethane: 990-063-002
Seal kit - Cartridge	Viton: 990-063-006

CONFIGURATION OPTIONS

Model Code Example: DCEXCYN

CONTROL (X)	SPOOL CONFIGURATION (C)	SEAL MATERIAL (N)	MATERIAL/COATING
X piloto estándar	C Blocked Center	N Buna-N	Standard Material/Coating
	A A to T Center	E EPDM	/AP Stainless Steel, Passivated
	B B to T Center	V Viton	
	H Open Center		
	N P to A and B to T Center		
	R Regen Center		
	T Tandem Center		
	W A and B Bleed to T Center		
	Y A and B to T Center		