



3 4 6 3 5000psi(350 bar)

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-64A
	4
	200 - 760 L/min.
	350 bar
	9 bar
	6,9 cc
110 SUS (24 cSt)	30 cc/min. @70 bar
	41,3 mm
	474 - 508 Nm
	1.87 kg.
Seal kit - Cartridge	Buna: 990-064-007
Seal kit - Cartridge	EPDM: 990-064-014
Seal kit - Cartridge	Polyurethane: 990-064-002
Seal kit - Cartridge	Viton: 990-064-006
Seal kit - Cartridge	Buna: 990-064-007
Seal kit - Cartridge	EPDM: 990-064-014
Seal kit - Cartridge	Polyurethane: 990-064-002
Seal kit - Cartridge	Viton: 990-064-006

OPTION SELECTION EXAMPLE: DCFCXCN

(X)	(C)	(N)	MATERIAL/COATING
X	C	N	Standard Material/Coating
	A A-T	E EPDM	/AP
	B B-T	V	
	H		
	N		
	R P-A-B		
	T P-T		
	W A B T		
	X		
	Y A-B-T		

TECHNICAL FEATURES

- 5000psi 350bar x y 5 6
-
-
- 5,6
- EPDM
-
- Sun

PERFORMANCE CURVES

