



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-64A
Series	4
Capacity	320 - 480 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	9 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	14 cc
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Model Weight	1.85 kg.
Seal kit - Cartridge	Buna: 990-064-007
Seal kit - Cartridge	Polyurethane: 990-064-002
Seal kit - Cartridge	Viton: 990-064-006
Seal kit - Cartridge	Buna: 990-064-007
Seal kit - Cartridge	Polyurethane: 990-064-002
Seal kit - Cartridge	Viton: 990-064-006

OPTION SELECTION EXAMPLE: DCFDXCN

CONTROL

(X)

SPOOL CONFIGURATION

(C)

SEAL MATERIAL

(N)

X piloto estándar

C Blocked Crossover

N Buna-N

H Open Crossover

V Viton

X P to B and A to T Crossover

PERFORMANCE CURVES

