



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-52A
Series	2
Capacity	80 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	10,5 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,82 cc
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-052-007
Seal kit - Cartridge	Viton: 990-052-006

# OPTION SELECTION EXAMPLE: DDDCXCN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	C Blocked Center	N Buna-N	Standard Material/Coating
	B B to T Center or B to T	V Viton	IAP Stainless Steel, Passivated
	D Blocked Center, Regen, P to B and A to T		
	H Open Center		
	R Regen Center		
	T Tandem Center		
	W A and B Bleed to T Center, Restrictive		
	Y A and B to T Center		

## PERFORMANCE CURVES



