



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-52A
Series	2
Capacity	80 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	10,5 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,82 cc
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-052-007
Seal kit - Cartridge	Viton: 990-052-006
Seal kit - Cartridge	Buna: 990-052-007
Seal kit - Cartridge	Viton: 990-052-006

OPTION SELECTION EXAMPLE: DDDCXCYN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	C Blocked Center	N Buna-N	Standard Material/Coating
	B B to T Center D Blocked Center, Regen, P to B and A to T H Open Center R Regen Center T Tandem Center W A and B Bleed to T Center, Restrictive Y A and B to T Center	V Viton	/AP Stainless Steel, Passivated

PERFORMANCE CURVES



