



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	SC-10-02
Series	1C
Capacity	60 L/min.
Maximum Operating Pressure	350 bar
Typical Valve Leakage at 110 SUS (24cSt)	15 drops/min. @1600 psi
Response Time - Typical	300 ms
Solenoid Tube Diameter	19 mm
Coil Nut Torque	4,8 - 5,3 Nm
Valve Hex Size	25,4 mm
Valve Installation Torque	39 - 42 Nm
Model Weight	0.28 kg.
Seal kit - Cartridge	Buna: 99C-102-007
Seal kit - Cartridge	Viton: 99C-102-006
Seal kit - Cartridge	Buna: 99C-102-007
Seal kit - Cartridge	Viton: 99C-102-006

OPTION SELECTION EXAMPLE: DGUAXCN

CONTROL	(X)	SPOOL CONFIGURATION	(C)	SEAL MATERIAL	(N)	BOBINA
<input checked="" type="checkbox"/> No Manual Override		<input checked="" type="checkbox"/> normalmente cerrado		<input checked="" type="checkbox"/> Buna-N		<input checked="" type="checkbox"/> No coil
<input type="checkbox"/> Manual Override (Push with Detent)		<input type="checkbox"/> normalmente abierto				

PERFORMANCE CURVES

