



## CONFIGURATION

### NOTES:

Modifier

Accessories" section.

- For check valve application, use only with CX\*A check valves - free flow nose to side.
- **Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

- Stack height value in technical data table includes seal retainer plate.
- This installation requires a retainer and seal kit which are purchased separately. See "Related

### MODIFIER

(/S3)

|            |  |
|------------|--|
| <b>/S3</b> | 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer              |
|            | 6061-T651 Aluminum, Buna-N   |
| <b>/11</b> | 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I  |
| <b>/10</b> | 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II |
| <b>/S</b>  | 65-45-12 Ductile Iron, Buna-N, Dewatering Oil                                    |
| <b>/S4</b> | 65-45-12 Ductile Iron, Buna-N, Chem. Black                                       |