



CONFIGURATION

NOTES: <small>Modifier</small>	
	<ul style="list-style-type: none"><li>Stack height value in technical data table includes seal retainer plate.</li><li>This installation requires a retainer and seal kit which are purchased separately. See "Related Accessories" section.</li></ul>
	<ul style="list-style-type: none"><li>For check valve application, use only with CX*A check valves - free flow nose to side.</li><li><b>Important:</b> Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.</li></ul>

MODIFIER (IS3)

IS3	65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
	6061-T651 Aluminum, Buna-N
I11	6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
I10	6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
IS	65-45-12 Ductile Iron, Buna-N, Dewatering Oil
IS4	65-45-12 Ductile Iron, Buna-N, Chem. Black