



3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-11A |
| | 1 |
| | 60 L/min. |
| | 350 bar |
| | 28 bar |
| | 0,16 cc |
| 110 SUS (24 cSt) | 0,7 cc/min.@350 bar |
| | See Performance Data |
| | 0,8 mm |
| | 22,2 mm |
| | 41 - 47 Nm |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |

OPTION SELECTION EXAMPLE: DKDDEHN

(E)

(H)

(N)

E 4-SAE

H 400 psi (28 bar)

N
V

TECHNICAL FEATURES

- 1 2 5000 psi (350 bar) 400 psi (30 bar)
- SAE 4 10 / 0.7 cc/min Sun DAA*-.***
- 1 2 5000psi 10 / 350bar 0,7 cc/min
- 145 psi 10 bar
- 1 2 3
- 5000 psi (350 bar)
- Sun /

PERFORMANCE CURVES

