



3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	60 L/min.
	350 bar
	28 bar
110 SUS (24 cSt)	0,7 cc/min.@350 bar
	See Performance Data
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: DKDPLAN

	(L)	(A)	(N)	MATERIAL/COATING
L				
C	-	A 400 - 3000 psi (28 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
K		B 400 - 1500 psi (28 - 105 bar), 1000 psi (70 bar)	E EPDM	/AP
		W 400 - 4500 psi (28 - 315 bar), 1000 psi (70 bar)	V	/LH -

TECHNICAL FEATURES

- 1 2 5000 psi (350 bar) 3
-
- 85%
- 1 2 3 4 3 4
- 1 2 5000psi 10 / 350bar 0,7 cc/min
- 5000 psi (350 bar)
- Sun /

PERFORMANCE CURVES

