



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-22A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	20 bar
Control Pilot Flow	See Performance Data
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

# OPTION SELECTION EXAMPLE: DKFPLAN

**CONTROL**

(L)

**ADJUSTMENT RANGE**

(A)

**SEAL MATERIAL**

(N)

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set

- A** 250 - 3000 psi (18 - 210 bar), 1000 psi (70 bar) Standard Setting
- B** 250 - 1500 psi (18 - 105 bar), 1000 psi (70 bar) Standard Setting
- W** 250 - 4500 psi (18 - 315 bar), 1000 psi (70 bar) Standard Setting

- N** Buna-N
- V** Viton

## PERFORMANCE CURVES

