



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-22A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	20 bar
Control Pilot Flow	See Performance Data
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Pilot Control Cavity	T-8A
Pilot Control Valve Hex Size	22,2 mm
Pilot Control Valve Installation Torque	27 - 33 Nm
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Model Weight	0.26 kg.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

OPTION SELECTION EXAMPLE: DKFR8HN

MINIMUM PILOT PRESSURE

(H) SEAL MATERIAL

(N)

H 300 psi (20 bar)

N Buna-N

E EPDM

V Viton

PERFORMANCE CURVES

