



3

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	240 L/min.
	350 bar
	20 bar
	0,82 cc
110 SUS (24 cSt)	0,7 cc/min.@350 bar
	31,8 mm
	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

# OPTION SELECTION EXAMPLE: DKHSXHN

	(X)	(H)	(N)	MATERIAL/COATING
X	H	300 psi (20 bar)	N	Standard Material/Coating
			E	/AP
			V	/LH -

## TECHNICAL FEATURES

- 1 2 5000 psi (350 bar) 300 psi (20 bar)
- 1 2 3 4 3 4
- 
- 1 2 5000psi 10 / 350bar 0,7 cc/min
- 145 psi 10 bar
- EPDM
- 1 2
- 5000 psi (350 bar)
- Sun /

## PERFORMANCE CURVES

