



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-150A
Series	0
Capacity	15 L/min.
Maximum Operating Pressure	210 bar
Typical Valve Leakage at 110 SUS (24 cSt) from port 1 to port 3	50 cc/min.@210 bar
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Solenoid Tube Diameter	16 mm
Valve Hex Size	19,1 mm
Valve Installation Torque	35 - 40 Nm
Model Weight	0.19 kg.
Seal and nut kit - Coil	Viton: 990-740-006
Seal kit - Cartridge	Buna: 990-150-007
Seal kit - Cartridge	Viton: 990-150-006
Seal kit - Cartridge	Buna: 990-150-007
Seal kit - Cartridge	Viton: 990-150-006

OPTION SELECTION EXAMPLE: DMBDXAN

CONTROL	(X)	SPOOL CONFIGURATION	(A)	SEAL MATERIAL	(N)	BOBINA	(812L)
X No Manual Override		A Normally Open 1 to 2, Closed 2 to 3		N Buna-N		No Coil	
P Manual Pull Override		N Normally Open 2 to 3, Closed 1 to 2		V Viton			

PERFORMANCE CURVES

