



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-150A
Series	0
Capacity	15 L/min.
Maximum Operating Pressure	350 bar
Typical Valve Leakage at 110 SUS (24 cSt) Inlet on 1	164 cc/min.@350 bar
Typical Valve Leakage at 110 SUS (24 cSt) Inlet on 2 or 3	82 cc/min.@350 bar
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Solenoid Tube Diameter	16 mm
Valve Hex Size	19,1 mm
Valve Installation Torque	35 - 40 Nm
Model Weight	0.19 kg.
Seal and nut kit - Coil	Viton: 990-740-006
Seal kit - Cartridge	Buna: 990-150-007
Seal kit - Cartridge	Viton: 990-150-006
Seal kit - Cartridge	Buna: 990-150-007
Seal kit - Cartridge	Viton: 990-150-006

# OPTION SELECTION EXAMPLE: DMBFXAN

<b>CONTROL</b>	<b>(X)</b> <b>SPOOL CONFIGURATION</b>	<b>(A)</b> <b>SEAL MATERIAL</b>	<b>(N)</b> <b>BOBINA</b>
<b>X</b> No Manual Override	<b>A</b> Normally Open 1 to 2, Closed 1 to 3	<b>N</b> Buna-N	No coil
<b>P</b> Manual Pull Override	<b>N</b> Normally Open 2 to 3, Closed 1 to 2	<b>E</b> EPDM	
		<b>V</b> Viton	

## PERFORMANCE CURVES

