



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-150A
Series	0
Capacity	15 L/min.
Maximum Operating Pressure	350 bar
Typical Valve Leakage at 110 SUS (24 cSt) Inlet on 1	164 cc/min.@350 bar
Typical Valve Leakage at 110 SUS (24 cSt) Inlet on 2 or 3	82 cc/min.@350 bar
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Solenoid Tube Diameter	16 mm
Valve Hex Size	19,1 mm
Valve Installation Torque	35 - 40 Nm
Model Weight	0.19 kg.
Seal and nut kit - Coil	Viton: 990-740-006
Seal kit - Cartridge	Buna: 990-150-007
Seal kit - Cartridge	Viton: 990-150-006

OPTION SELECTION EXAMPLE: DMBFXAN

CONTROL	(X) SPOOL CONFIGURATION	(A) SEAL MATERIAL	(N) BOBINA
X No Manual Override	A Normally Open 1 to 2, Closed 1 to 3	N Buna-N	No coil
P Manual Pull Override	N Normally Open 2 to 3, Closed 1 to 2	E EPDM	
		V Viton	

PERFORMANCE CURVES

