



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.@210 bar
Operating Torque	1,2 Nm
Seal kit - Cartridge	Buna: 990-411-007
Seal kit - Cartridge	Viton: 990-411-006
Seal kit - Cartridge	Buna: 990-411-007
Seal kit - Cartridge	Viton: 990-411-006

**CONFIGURATION OPTIONS**

Model Code Example: **DMDMLAN**

CONTROL	(L)	SPOOL CONFIGURATION	(A)	SEAL MATERIAL	(N)
<b>L</b> Twist/Lock (Detent) Manual Override		<b>A</b> Normally Open 1 to 2, Closed 2 to 3		<b>N</b> Buna-N	
<b>D</b> Twist/Lock (Dual) Manual Override		<b>B</b> Normally Open 1 to 2, Closed 2 to 3, Closed Transition		<b>V</b> Viton	
<b>T</b> Twist (Momentary) Manual Override		<b>N</b> Normally Open 2 to 3, Closed 1 to 2			
		<b>P</b> Normally Open 1 to 3, Closed 1 to 2			
		<b>R</b> Normally Open 2 to 3, Closed 1 to 2, Closed Transition			