



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	45 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.@210 bar
Operating Torque	1,2 Nm
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990-411-007
Seal kit - Cartridge	Viton: 990-411-006
Seal kit - Cartridge	Buna: 990-411-007
Seal kit - Cartridge	Viton: 990-411-006

# OPTION SELECTION EXAMPLE: DMDMLAN

**CONTROL**

- L** Twist/Lock (Detent) Manual Override
- D** Twist/Lock (Dual) Manual Override
- T** Twist (Momentary) Manual Override

**(L) SPOOL CONFIGURATION**

- A** Normally Open 1 to 2, Closed 2 to 3
- B** Normally Open 1 to 2, Closed 2 to 3, Closed Transition
- N** Normally Open 2 to 3, Closed 1 to 2
- P** Normally Open 1 to 3, Closed 1 to 2
- R** Normally Open 2 to 3, Closed 1 to 2, Closed Transition

**(A) SEAL MATERIAL**

- N** Buna-N
- V** Viton

**(N)**

## PERFORMANCE CURVES

