



* An additional 2.00 (50,8) clearance needed for coil installation and removal

* Coil code is appended to the cartridge base model code. See CONFIGURATION section.

in (mm)

2 3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	SC-08-03
	0C
	15 L/min.
	250 bar
110 SUS (24 cSt)	80,2 cc/min.@250 bar
	50 ms
	.51 in.
	4,8 - 5,3 Nm
	24 mm
	28 - 31 Nm
	0,20 kg
Seal kit - Cartridge	Buna: 99C-083-007
Seal kit - Cartridge	Viton: 99C-083-006
Seal kit - Cartridge	Buna: 99C-083-007
Seal kit - Cartridge	Viton: 99C-083-006

OPTION SELECTION EXAMPLE: DMTAXAHN

	(X)	(A)	(N)
X	A 1-2 1-3	N	
L ()	H 1-2 1-3		
	N 2-3 1-2		
	P 1-3 1-2		

TECHNICAL FEATURES

-
- 3600 psi (250 bar)
-
-
-
- 3600 psi (250 bar)
- 22 lbf ft (30 Nm)
-
- IP67

PERFORMANCE CURVES



