



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Typical Valve Leakage at 110 SUS (24 cSt) - Except N Spool	66 cc/min.@350 bar
Typical Valve Leakage at 110 SUS (24 cSt) - N Spool, Inlet on 3	115 cc/min.@350 bar
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Seal kit - Cartridge	Buna: 990-030-007
Seal kit - Cartridge	Viton: 990-030-006
Seal kit - Cartridge	Buna: 990-030-007
Seal kit - Cartridge	Viton: 990-030-006

CONFIGURATION OPTIONS

Model Code Example: DNBFXNN

CONTROL	(X)	SPOOL CONFIGURATION	(N)	SEAL MATERIAL	(N)	BOBINA	(812)
X No Manual Override		N Through, Shift to Cross		N Buna-N		No Coil	
P Manual Pull Override		C Closed, Shift to Through		E EPDM			
		D Closed, Shift to Cross		V Viton			
		E Cross, Shift to Closed					
		T Tandem, Shift to Through					
		V Cross, Shift to Tandem					