



2 4

### SWITCH SPECIFICATIONS

	20-30 VDC
	-25 to 80 °C
	≥ 50g, 0-500 impulses/sec
	>50 g, 1ms
	≤ 400 mA, Duty Ratio 100%
	Yes, Load Short Unlimited
	≤ 25 ms
	≤ .002 in.
- 0-80 °C ≤ ±	0,1 mm
	DIN EN 61000-6-1/2/3/4
	M12 X 1 (4) Pin
	IP65
Seal kit - Cartridge	Buna: 990-431-007
Seal kit - Cartridge	Viton: 990-431-006

### TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-31A
	1
	30 L/min.
	350 bar
110 SUS (24 cSt)	160 cc/min.@210 bar
	50 ms
	15,000 max. cycles/hr
	19 mm
	22,2 mm
	41 - 47 Nm
	0.97 kg.
Seal kit - Cartridge	Buna: 990-431-007
Seal kit - Cartridge	Viton: 990-431-006

# OPTION SELECTION EXAMPLE: DNCAZXN224

(X)

(N)

(224)

<b>X</b>	<b>N</b>	<b>224</b> DIN 43650 A 24 VDC
A A-T	V	<b>212</b> DIN 43650 A 12 VDC
B B-T		<b>912</b> Deutsch DT04-2P 12 VDC
C		<b>924</b> Deutsch DT04-2P 24 VDC
J		
L P-A B-T		
S P-A-B		
T P-T		
W A B T		
Z A-B-T		

## TECHNICAL FEATURES

- 
- CE
- 
- 3 1
- 5000 psi (350 bar)
- 
- 
- 
- 
- Sun /

## PERFORMANCE CURVES



