



3 4

A

3 P

2 A

4 B

1 T

B

3 4

2 1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-31A
	1
	20 L/min.
	350 bar
110 SUS (24 cSt)	160 cc/min. @210 bar
	50 ms
	15,000 max. cycles/hr
	19 mm
	22,2 mm
	41 - 47 Nm
Seal and nut kit - Coil	Viton: 990-770-006
Seal kit - Cartridge	Buna: 990-431-007
Seal kit - Cartridge	EPDM: 990-431-014
Seal kit - Cartridge	Viton: 990-431-006
Seal kit - Cartridge	Buna: 990-431-007
Seal kit - Cartridge	EPDM: 990-431-014
Seal kit - Cartridge	Viton: 990-431-006

: • 2

A

B

OPTION SELECTION EXAMPLE: DNDXCYN

(X)	(C)	(N)	
X	C	N	
	A A-T	E EPDM	212 DIN 43650 A 12 VDC
	B B-T	V	224 DIN 43650 A 24 VDC
	H		912 Deutsch DT04-2P 12 VDC
	R P-A-B		924 Deutsch DT04-2P 24 VDC
	T P-T		
	W A B T		
	Y A-B-T		

TECHNICAL FEATURES

- 5000 psi (350 bar)
-
- 2 A 1 T
- EPDM
- /
-
- Sun 1
- IP69K
- Sun /

PERFORMANCE CURVES

