



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	60 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	28 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Pilot Volume Displacement	0,16 cc
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.14 kg.
Seal kit - Cartridge	Buna: 990-311-007
Seal kit - Cartridge	Viton: 990-311-006
Seal kit - Cartridge	Buna: 990-311-007
Seal kit - Cartridge	Viton: 990-311-006

OPTION SELECTION EXAMPLE: DODCEHN

CONTROL	(E) MINIMUM PILOT PRESSURE	(H) SEAL MATERIAL	(N) MATERIAL/COATING
E External 4- <small>SAE</small> Drain Port	H 400 psi (28 bar)	N Buna-N	Standard Material/Coating
X Standard Pilot, Atmospheric Vent		V Viton	/AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

