



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|---------------------------|
| Maximum Operating Pressure | 350 bar |
| Minimum Pilot Pressure Required to Shift Valve | 28 bar |
| Control Pilot Flow | See Performance Data |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,7 cc/min.@350 bar |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |

CONFIGURATION OPTIONS

Model Code Example: DODPLAN

CONTROL

(L)

ADJUSTMENT RANGE

(A)

SEAL MATERIAL

(N)

L Standard Screw Adjustment

A 400 - 3000 psi (28 - 210 bar), 1000 psi (70 bar)
Standard Setting

B 400 - 1500 psi (28 - 105 bar), 1000 psi (70 bar)
Standard Setting

W 400 - 4500 psi (28 - 315 bar), 1000 psi (70 bar)
Standard Setting

N Buna-N

V Viton