



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|---------------------------|
| cavidad | T-21A |
| Series | 1 |
| Capacity | 60 L/min. |
| Maximum Operating Pressure | 350 bar |
| Minimum Pilot Pressure Required to Shift Valve | 28 bar |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,7 cc/min.@350 bar |
| Pilot Passage into Valve | 0,8 mm |
| Pilot Volume Displacement | 0,16 cc |
| Valve Hex Size | 22,2 mm |
| Valve Installation Torque | 41 - 47 Nm |
| Model Weight | 0.16 kg. |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | EPDM: 990-021-014 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |

OPTION SELECTION EXAMPLE: DODSXHN

| CONTROL | (X) | MINIMUM PILOT PRESSURE | (H) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|---------|-----------------|------------------------|------------------|---------------|--------|---------------------------------|
| X | piloto estándar | H | 400 psi (28 bar) | N | Buna-N | Standard Material/Coating |
| | | | | E | EPDM | /AP Stainless Steel, Passivated |
| | | | | V | Viton | /LH Mild Steel, Zinc-Nickel |

PERFORMANCE CURVES

