



3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	60 L/min.
	350 bar
	28 bar
	0,16 cc
110 SUS (24 cSt)	0,7 cc/min.@350 bar
	0,8 mm
	22,2 mm
	41 - 47 Nm
	0.16 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	EPDM: 990-021-014
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	EPDM: 990-021-014
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: DODSXHN

	(X)	(H)	(N)	MATERIAL/COATING
X	H	400 psi (28 bar)	N	Standard Material/Coating
			E EPDM	/AP
			V	/LH -

TECHNICAL FEATURES

- 1 2 5000 psi (350 bar) 400 psi (30 bar)
- EPDM
- 145 psi 10 bar
- 1 2
- 1 2 3 4 3 4
-
- 1 2 5000psi 10 / 350bar 0,7 cc/min
- 5000 psi (350 bar)
- Sun /

PERFORMANCE CURVES

