



3

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-2A
	2
	120 L/min.
	350 bar
	20 bar
	0,33 cc
110 SUS (24 cSt)	0,7 cc/min.@350 bar
	See Performance Data
	28,6 mm
	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

# OPTION SELECTION EXAMPLE: DOFDEHN

(E)

(H)

(N)

**E** 4-SAE

**H** 300 psi (20 bar)

**N**

V

## TECHNICAL FEATURES

- 1 2 5000 psi (350 bar) 300 psi (20 bar)
- 1 2
- 1 2 5000psi 10 / 350bar 0,7 cc/min
- 145 psi 10 bar
- SAE 4 10 / 0.7 cc/min Sun DAA\*-\*\*\*
- 1 2 3
- 5000 psi (350 bar)
- Sun /

## PERFORMANCE CURVES

